

8473101001

GMT TPA Fuse Panel

Total Front Access



Positions Per Bus
4 TPA - 5 GMT

Max Per Position
50A TPA - 15A GMT

Bus Capacity
150 Amps

GENERAL	
Dimensions	19.00" W x 3.50" H x 6.625" D
Rack Space	2U
Weight	6.0 lbs.
Mounting	Universal 19", 23", or Wall-Mountable, WECCO/EIA
Mtg. Pos.	Front or Rear Flush, 2.835" Offset
Finish	Black Textured Powder Coat
ELECTRICAL	
Input	Nominal Voltage -/+24-48V DC
	Voltage Range -/+19-60V DC
	Number of Buses 2
	Intr. Device Rating 175 Amps
Output	Max Fuse Rating TPA Fuse - 50 Amp GMT Fuse - 15 Amp
	Continous Load Rating TPA Fuse - 40 Amps GMT Fuse - 10.5 Amps
ALARMING	
Indicators	Green (Power)/Red (Alarm)
Function	Form C relay contacts for remote fuse and power fail indication
Conn. Type	Solderless Wire Wrap (18 to 30 AWG)
Rating	DC 30W/AC 50VA



CONNECTIONS		
Input	2 Hole Lug	1/4" stud x 5/8" spacing
	Wire Range	Up to 2/0 AWG
	Max. Terminal Width	0.640"
	Tightening Torque	40 in-lb (2.7 Nm)
Output	Barrier Strip Output	TPA - #8 Sems Screw, GMT #6 Sems Screw
	Wire Range	TPA - 6 to 22 AWG GMT - 10 to 22 AWG
	Max. Terminal Width	TPA - 0.500" / GMT - 0.312"
	Tightening Torque	10 in-lb GMT - 16 in-lb TPA
Ground Bus	2 Hole Lug	1/4" stud x 1" spacing
	Wire Range	6 AWG lug supplied with panel

ENVIRONMENT	
Short Term Op Temp	-40° C to +70° C
Ambient	Up to 65° C
Store Temp	-40° C to +70° C
Humidity	0 to 95% non-condensing
Power Dissipation	42.59 Watts max

STANDARDS	
Safety <small>(Listed)</small>	UL 60950-1/UL 1801/CSA C22.2 No.60950-1/EN 60950-1/IEC 60950-1
Telcordia	NEBS Level 3 (GR-63/GR-1089) and GR-3108 Class 3 (w/o salt fog testing)

Front Access, 5/4 GMT TPA Fuse Panel, Stud In, Barrier Out

8473101001



NOTES

CLEI Code: PWPYAC5RRA. Go to www.trimm-inc.com for a complete list of the fuses to order with this panel.