


Product Specifications: 7671100001 Fuse Panel			
Mechanical	Dimensions	23" W x 3.484" H x 14.5" D	
	Rack Spaces	2 (2U)	
	Weight	20 Lbs. (w/without fuses/breakers)	
	Mounting	23" WECCO/EA spacing	
	Offset Mounting Positions	Flush, 4" or 5" offset	
Electrical	Input	Voltage	-/+ 24 TO 48 VDC
		Number of Buses	2 (A/B)
		Current	600 Amps max. per bus (1200 Amps total)
	Output	Interrupt Device Rating	750 Amps max.
		Single Pole	Up to 125 Amps (see fuse/breaker table)
Connections	Input	Dual Pole	Up to 250 Amps (see fuse/breaker table)
		Continuous Load Rating	100 Amp (single pole) or 200 Amp (dual pole)
	Output	Number of Single/Dual Positions	Up to 10 single pole or 5 dual pole per bus
		Fuse/Breaker Types Accepted	Bussmann® TPS, TPC, TPW, Littelfuse® TLS, 1 and 2 pole circuit breakers
	Return Bus	2 Hole Compression Lugs	3/8" stud x 1" center-center spacing
		Wire Range	Up to 750 kcmil (up to 2 lugs per bus)
	Earthing (Chassis GND)	Max. Terminal Width	2" maximum
		Wire Range	Up to 2/0 Awg.
	Environment	2 Hole Compression Lugs	1/4" captive studs x 5/8" center-center spacing
		Wire Range	Up to 750 kcmil
Alarming	2 Hole Compression Lugs	1/4" captive nuts x 5/8" center-center spacing	
	Wire Range	Up to 4/0 Awg (1" max. width)	
Standards	Short Term Operating Temperature	-5° C to +50° C	
	Max. Recommended Ambient	Up to +50° C	
	Storage Temperature	-40° C to +70° C	
Telcordia (NEBS)	Relative Humidity	0-95% noncondensing	
	Indicators	Bi-color led Green (power) Red (alarm)	
	Alarm Capability	Form "C" contacts 1 set for power, 1 set for fuse/breaker fail	
	Connection Type	Solderless wrap (18 to 30 Awg) min. 5 turns	
Safety (Recognized)	UL 60950-1, UL 1801, CSA C22.2 No. 60950-1		
	EN 60950-1, IEC 60950-1		
NEBS Level 3 Certified			
Whats included: 4 x #12-24 rack mounting screws, input connection hardware (locking bolts and washers for battery/return connections), chassis ground connection hardware (locking bolts and washers), and output hardware (locking nuts). Fasteners for load equipment return connections not included.			



VERIZON MATERIAL ID	
MATERIAL ID	TRIMM PART NUMBER
11066359	7671100001L

The information on this document is proprietary information that is property of Trimm, inc. and shall not be reproduced or its contents disclosed in any manner whatsoever without the express written consent from Trimm, Inc. Due to continuous product development, specifications may change from those listed. Call Trimm, inc. for information

TOLERANCES: -/+ .015 ON OVERALL PART SIZE, -/+ .010 FROM ANY BEND TO THE CENTERLINE OF ANY HOLE OR CUTOUT, -/+ .005 FROM CENTERLINE TO CENTERLINE ON ANY HOLE OR CUTOUT

NOTES:
 1-Dimensions are shown in Inches [mm].
 2-Panel includes 20 x 80Amp circuit breakers.

APPROVED BY:	DRAWN BY: BRIAN BURCH	DATE: 02/23/09	SIZE: B	DESCRIPTION: FUSE PANEL-10H/10H-0G/0G-DV 23" 2U W/20 80A BREAKERS	REV. A
			FILE CODE MKT	DRAWING NUMBER: 7671100001L	PAGE: 1
				TRIMM, INC. 407 RAILROAD ST. BUTNER, NC. PHONE: 1-800-298-7466 FAX: 1-919-575-6200	